



GROUND
 MUST CONNECT TO BATTERY GROUND
 ALL FOUR FASTON TABS INTERNALLY CONNECTED
 MAY BE USED TO PROVIDE GROUND TO BALLAST AND MOTOR

LED
 TURNS ON WHEN EITHER HIGH OR LOW BEAM IS ACTIVATED
 WILL TURN OFF AFTER APPROXIMATELY 30 SECONDS

RED
 CONNECT TO BATTERY +12VDC

YELLOW
 CONNECT TO BALLAST +12V CONNECTION

WHITE
 CONNECT TO HEADLIGHT CIRCUIT LOW BEAM

BLUE
 CONNECT TO HEADLIGHT CIRCUIT HIGH BEAM
 CONNECT BI-XENON MOTOR HERE

ALL TERMINALS ARE FASTON TYPE

1/4" X .032"

RECOMMEND TYCO/AMP PART NUMBER

520988-2 RECEPTACLE 18-22 AWG

521637-2 RECEPTACLE (2X) 18-22 AWG

**FOR USE ON VEHICLES EQUIPPED WITH
 WARNING LIGHTS ONLY**

INQUIRE ABOUT PRE MADE PLUG AND PLAY
 WIRING HARNESS

AR-02D CONNECTION DIAGRAM

APPLICATIONS DRAWING
 AR-02D_D01A 032709

AR-02D CONNECTION DIAGRAM



ASM LIGHTING
 405 UNITED DR.
 NEW SMYRNA BEACH, FL 32168
 asmlighting.com